



FLEXES

We can provide a wide variety of flexes to suit all applications. There are three different types of flexes available. Our standard flex is suitable for nearly all applications and is available in many different lengths and bore sizes. The inner braided flex can be used to counteract whistling problems, while our strengthened flex is especially suited to applications where there is a lot of movement through the flex.

Please contact us for price and availability (trade only).

Product Support: +44 (0)1623 663802

Email: support@bmcatalysts.com

Web: www.bmcatalysts.com

EXCEEDING EXPECTATIONS





STANDARD

Part No.	Diameter (mm)	Length (inch)
FL38X4	38	4
FL45X4	45	4
FL45X6	45	6
FL45X8	45	8
FL45X200	45	8
FL48X6	48	6
FL48X8	48	8
FL51X6	51	6
FL51X8	51	8
FL51X10	51	10
FL54X6	54	6
FL54X8	54	8
FL54X10	54	10
FL54X13	54	13
FL57X2	57	2
FL57X6	57	6
FL57X8	57	8
FL64X2	64	2
FL64X8	64	8
FL64X10	64	10
FL76X6	76	6

INNER BRAIDED

Part No.	Diameter (mm)	Length (inch)
FL51X4IB	51	4
FL51X10IB	51	10
FL54X10IB	54	10
FL64X6IB	64	6
FL76X6IB	76	6

INNER LOCK CONNECTOR

Part No.	Diameter (mm)	Length (inch)
FL48X200ILC	48	8

STRENGTHENED

Part No.	Diameter (mm)	Length (inch)
FL38X6ILOK	38	6
FL42X4ILOK	42	4
FL45X3ILOK	45	3
FL45X4ILOK	45	4
FL45X6ILOK	45	6
FL45X8ILOK	45	8
FL45X10ILOK	45	10
FL48X4ILOK	48	4
FL48X6ILOK	48	6
FL51X3ILOK	51	3
FL51X4ILOK	51	4
FL51X6ILOK	51	6
FL51X8ILOK	51	8
FL54X4ILOK	54	4
FL54X6ILOK	54	6
FL57X4ILOK	57	4
FL57X6ILOK	57	6
FL57X8ILOK	57	8
FL64X100ILOK	64	4
FL64X150ILOK	64	6
FL64X8ILOK	64	8
FL76X110ILOK	76	4
FL76X6ILOK	76	6
FL76X8ILOK	76	8

Product Support: +44 (0)1623 663802

Email: support@bmcatalysts.com

Web: www.bmcatalysts.com

EXCEEDING EXPECTATIONS

